

Sure Klean® Weather Seal Blok-Guard® & Graffiti Control II Water Repellent Specification

Specifier Note: The information provided below is intended to guide the Architect in developing specifications for products manufactured by PROSOCO, Inc. and should not be viewed as a complete source of information about the product(s). The Architect should always refer to the Product Data Sheet and MSDS for additional recommendations and for safety information.

Specifier Note: Paragraph below is for PART 1 GENERAL, Quality Assurance.

Test Area

Test a minimum 4 ft. by 4 ft. area on each type of masonry. Use the manufacturer's application instructions. Let protective treatment test area cure before inspection. Keep test panels available for comparison throughout the protective treatment project.

Specifier Note: Paragraphs below are for PART 2 PRODUCTS, Manufacturers and Products.

Manufacturer: PROSOCO, Inc., 3741 Greenway Circle, Lawrence, KS 66046. Phone: (800) 255-4255; Fax: (785) 830-9797. E-mail: CustomerCare@prosoco.com

Product Description

Sure Klean® Weather Seal Blok-Guard® & Graffiti Control II is a clear-drying, water-based silicone emulsion for weatherproofing concrete block and other porous masonry materials and protecting them from graffiti attacks without altering the natural appearance.

Blok-Guard® & Graffiti Control II protects exterior walls exposed to normal weathering. Graffiti removal from treated surfaces is fast and easy using Defacer Eraser® Graffiti Wipe.

Technical Data

FORM: Milky white liquid

SPECIFIC GRAVITY: 1.00

ACTIVE CONTENT: 6%

pH: N/A

WT./GAL.: 8.32 LBS.

FLASH POINT: >212°F (>100°C)

FREEZE POINT: 34°F (1°C)

VOC CONTENT: Complies with all known federal, state and district AIM VOC Standards.

Limitations

- Not suitable for extremely dense or polished surfaces.
- Not suitable for asphaltic surfaces.
- Not recommended for below-grade applications.
- Will not prevent water penetration through structural cracks, defects or open joints.
- May be difficult to remove from adjacent surfaces. Always protect.
- Not recommended for horizontal surfaces.
- Not appropriate for application to painted surfaces.

Specifier Note: Paragraphs below are for PART 3 EXECUTION, Installation.

Application

Before applying, read "Preparation" and "Safety Information" sections in the Manufacturer's Product Data Sheet for Weather Seal Blok-Guard® & Graffiti Control II. Refer to the Product Data Sheet for additional information about application of Blok-Guard® & Graffiti Control II. Do not dilute or alter.

For best results, apply Blok-Guard® & Graffiti Control II “wet-on-wet” to a visibly dry and absorbent surface.

Spray

1. Saturate from the bottom up.
2. Let the first application penetrate for 2-3 minutes. Re-saturate. Less will be needed for the second application.

Brush or Roller:

1. Saturate uniformly.
2. Let Blok-Guard® & Graffiti Control II penetrate for 2-3 minutes. Re-saturate.
3. Brush out heavy runs and drips that don't penetrate.

Dense, Smooth Surface Application Instructions

Apply a single coat. Use enough Blok-Guard® & Graffiti Control II to completely wet the surface without creating drips, puddles or rundown. DO NOT OVER APPLY. Test for application rate.

Porous Surface Application Instructions

Some surfaces may need an additional coat of Blok-Guard® & Graffiti Control II for maximum protection. Apply the second wet-on-wet coat as soon as the first application is dry to the touch or within one hour. Allowing more than one hour between coats could reduce the effectiveness of the second coat or cause darkening.

Treated surfaces dry to touch in 1 hour. Protect surfaces from rainfall for 6 hours following treatment. Blok-Guard® & Graffiti Control II treatments gain its water repellency properties in 24 hours.

Graffiti Removal

Remove most types of graffiti with Defacer Eraser® Graffiti Wipe or Sure Klean® Fast Acting Stripper.